



# ACU 5020 for Mobile Uplinks

## Technical Specifications

### TECHNICAL SPECIFICATION

<b>Local Control</b>	Via local keypad Via Manual Control Unit ACU E110B SNG
<b>Remote Interface</b>	RS232 / LAN
<b>Motor Interface</b>	24 VDC servo drive
<b>Prime Power</b>	Single-phase 115/230 VAC, 50 to 60 Hz + 12 VDC for emergency control
<b>Environmental Specifications</b>	0 to +50°C (Indoor) 90% without condensation
<b>Position Encoding Interface</b>	Single-speed brushless resolver
<b>Power Consumption</b>	Max. 400 W (if all motors are running)
<b>Dimensions (L X W X H)</b>	482.6 mm (19") x 88 mm (2 RU) x 510 mm
<b>Weight</b>	10 kg

ND SATCOM  
E.ON Energy Research Center  
'dÄi'p|Zÿt^ZEGÿt^hÄEEÖ  
006e60/wwGÿEtÄÄ  
PHONE: +49 7545 939 0  
FAX: +49 7545 939 8780  
E-Mail: info@ndsatcom.com

/l Lb  
b5 / . /  
tl hb9  
a L5 9 9  
b5 / C 9  
tl hb9

[www.ndsatcom.com](http://www.ndsatcom.com)

ND SATCOM