



HIGH POWER AMPLIFIER 750W Standard KU-BAND Outdoor HPA 2713B

ND SATCOM has been a supplier to the SatCom industry for over three decades and has built up an excellent reputation for consistently developing high-end satellite communication products at competitive prices for customers in more than 130 countries worldwide. Our team of dedicated engineers works closely together with customers worldwide to develop, tailor and adapt our product portfolio to deliver innovative broadcast and network solutions that fit evolving market requirements with superior reliability and quality.

As a system integrator for broadcasters and military forces operating worldwide, we design both indoor and outdoor HPAs whose modular construction is compact, reliable, easy to service and high performing. Our products are designed to adapt development to your operational needs, thus providing highly secure, custom-engineered solutions that have long established us as a trusted and reliable partner in satellite communications.

Unrivalled RF Performance

Combines supreme power efficiency and low phase noise (typ. IESS 308/309) for a RF performance that is second to none.

Efficient and Reliable

Our Electrical Power Conditioners designed for satellites operate with very low in-rush current (110%) and active power factor correction. Thus the power consumption, weight, and dimensions of the ND SATCOM HPAs are best of breed.

Safe and Durable

For enhanced TWT longevity, the high voltage section is potted and all other electrical components are coated to protect against humidity and dust.

Compact

Its light-weight (only 36kg or 79lbs) and small dimensions make it ideal for both transportable and compact fixed uplink stations.

Easy to Maintain

All RF parameters can be monitored and controlled directly or by remote access.

Rapid Response

- Quick delivery
- After-Sales Support: typically 1-week turnaround time
- Made in Germany: EUR1 certificate / no ITAR restrictions

Options

- Integrated BUC and Linearizer
- Waveguide Switching System
- Remote control panel (outdoor versions)
- Water cooling
- Plug-in/plug-out exchange kit for CPI HPAs, including adaptation of interface protocol and all mechanical connections

ND SATCOM

powered by **ASP**

HPA 2713B

RF SPECIFICATIONS

Frequency Range	13.75 - 14.50 GHz	
Flange Power	> 630 W, > 58 dBm	
TWT Power	750 W Tube	
Gain at Rated Power	> 65 dB	
Small Signal Gain (10 dB OBO)	> 72 dB	
Gain Adjust	> 0 - 20 dB, min. step size 0.1 dB	
Gain Stability	< ±0.25 dB / °C / 24 hrs after 60 min warm-up	
Gain Slope	< 0.02 dB / MHz	
Gain Variation	< 1.0 dB / in any 80 MHz, < 2.5 dB / in any 500 MHz, < 5.5 dB / full band	
VSWR	< 1.3:1 Input < 1.2:1 Output (waveguide)	
Group Delay (in any 40 MHz)	< 0.01 ns / MHz linear, < 0.005 ns / MHz ² parabolic, < 0.5 ns ripple	
Intermodulation (two equal carriers at total output power)	Without Linearizer 2713B < -21 dBc at 6 dB below rated power	With Linearizer 2713BL < -30 dBc at 4 dB below rated power (meets ASTRA access agreement 6.4.2 for FSS Band with rated power -2dB)
AM/PM Conversion	< 2.5° / dB at 7 dB below rated power, < 6° / dB at rated output power	
Noise Figure	< 15 dB max	
Phase Noise	Meets IESS 308/309	
Noise and Spurious Emissions	< -65 dBW / 4 kHz (inband) < -120 dBW / 4 kHz 10.7..12.7 GHz < -115 dBW / 4 kHz 18.0..19.0 GHz	
Harmonic Output Suppression	< -80 dBc at rated output	

Physical

Input RF Connector	N-Jack Input / N-Jack Testport
Output RF Connector	WR 75 Waveguide Output, grooved, UNC 6/32
Dimensions (L X W X H)	294 x 233 x 649 mm
Weight	< 36 kg / 79 lbs
Cooling	forced air min. 200 m ³ /h

Monitor & Control

Serial Remote Interface	PT 851-00R12-10S50 RS422/RS485
Alarm / Mute Interface	PT 851-00R12-10S50
Parallel Remote Interface	PT 851-00R19-10S50
Automatic Level Control	Activation via RC Protocol

Electrical Specifications

AC Power	190 to 240 VAC / 50-60 Hz, single phase
Power Factor	> 95%
Power Consumption	< 2350 W max.
Inrush Current	< 110%
CE Directive	73/23/EEC, 92/31/EEC, 89/336/EEC and 1999/5/EC

Environmental Specifications

Temperature Range (operational)	-40°C to +50°C
Humidity	< 95% condensing at 40°C
Shock and Vibration	For normal commercial transport
Noise Level (cooling fan)	< 65 dBA measured in 1 m distance

HEADQUARTERS
 ND SatCom GmbH
 Graf-von-Soden-Strasse
 88090 Immenstaad
 Germany
 PHONE: +49 7545 939 0
 FAX: +49 7545 939 8780
 E-Mail: info@ndsatcom.com

CHINA
 ND SatCom (Beijing) Co. Ltd.
 PHONE: +86 10 6590 6869/6878

MIDDLE EAST
 ND SatCom FZE
 PHONE: +971 4886 5012

www.ndsatcom.com

ND SATCOM
 powered by 