

2.4 M MOBILE STATION

The ND SATCOM 2.4 m Mobile Station is the Satellite Communications solution of choice whenever a mobile uplink is needed, such as for disaster recovery, crisis management, emergency response or interim/backup uplink.

This Mobile Station with a 2.4 m antenna is self-supporting. It contains both a power generator and air conditioning/heating to function independently of local infrastructure. It also contains climate controlled vibration-cushioned 24RU rack space for electronic equipment and ample accessories space in the non-climate controlled area. Designed on a single-axle trailer, it can be easily transported.

NO SetCam

KEY FEATURES

- Built for autonomous field operation; self-supporting
- 10 kW power generator
- External power input including isolating transformer
- Air conditioning: 3 kW cooling and 2 kW heating capacity
- 24RU climate controlled rack space
- 2.4 m antenna capable of multiple frequency band
 (C. Ku. DBS and Ka)





TECHNICAL SPECIFICATIONS

SIZELXWXH

Container incl. stowed Antenna

Mounted on trailer

Weight

Transport

ENVIROMENTAL

Temperature

Wind

3,144 x 1,813 x 1,844 mm

max. 5,070 (min. 4,490) x 2,150 x 2,900 mm

up to 5,000 kg

On Trailer (MOT approved)

Detached from trailer in 20 ft ISO container

-30 °C up to +50 °C

20 m/s steady gusting up to 27 m/s

RF-SPECIFICATIONS

C-BAND	KU-BAND	K-BAND	KA-BAND
2 Port Circular	2 Port Linear	2 Port Linear	2 Port Circular
5.85 - 6.425	13.00 – 14.50	17.30 – 18.40	27.50 – 31.00
3.625 – 4.20	10.70 – 12.75	10.70 – 12.75	17.70 – 21.20
42.1@6.138	48.5@13.75	50.3@17.85	54.7@29.25
38.0@4.00	47.1@11.725	47.5@11.725	51.4@18.95
69.7	75.3	77.3	78.1
18.0@4.0	24.5@11.725	26.0@11.725	27.5@18.95
	2 Port Circular 5.85 - 6.425 3.625 - 4.20 42.1@6.138 38.0@4.00 69.7	2 Port Circular 2 Port Linear 5.85 - 6.425 13.00 - 14.50 3.625 - 4.20 10.70 - 12.75 42.1@6.138 48.5@13.75 38.0@4.00 47.1@11.725 69.7 75.3	2 Port Circular 2 Port Linear 2 Port Linear 5.85 - 6.425 13.00 - 14.50 17.30 - 18.40 3.625 - 4.20 10.70 - 12.75 10.70 - 12.75 42.1@6.138 48.5@13.75 50.3@17.85 38.0@4.00 47.1@11.725 47.5@11.725 69.7 75.3 77.3

ND SATCOM reserves the right to change specifications without notice.









HEADQUARTERS

ND SatCom GmbH Graf-von-Soden-Strasse 88090 Immenstaad Germany

PHONE: + 49 7545 939 0 FAX: + 49 7545 939 8780 E-Mail: info@ndsatcom.com

CHINA

ND SatCom (Beijing) Co. Ltd. PHONE: +86 10 6590 6869/6878

MIDDLEEAST

ND SatCom FZE PHONE: +971 4886 5012